



TRANSFORMADOR PADMOUNTED TRIFASICO - RADIAL										
CLASE 15/25 KV										
POTENCIA	LONGITUD CORTE	ALTURA CORTE	ANCHO CORTE	ALTURA CONCRETO	ANCHO CONCRETO		LONGITUD CONCRETO	LONGITUD TOTAL CR	ANCHO TOTAL CR	
					S/SW	SW2P			S/SW	SW2P
[KVA]	[mm] - [A]	[mm] - [B]	[mm] - [C]	[mm] - [D]	[mm] - [E]		[mm] - [F]	[mm] - [G]	[mm] - [H]	
30	1240	800	535	150	558	608	200	1640	1293	1343
50	1240	800	535	150	558	608	200	1640	1293	1343
75	1240	800	535	150	558	608	200	1640	1293	1343
100	1240	800	535	150	578	608	200	1640	1313	1343
125	1240	800	535	150	761	608	200	1640	1496	1343
150	1240	800	535	150	608	638	200	1640	1343	1373
200	1240	800	535	150	608	638	200	1640	1343	1373
250	1240	800	535	150	638	638	200	1640	1373	1373
300	1240	800	535	150	739	759	200	1640	1474	1494
400	1240	800	535	150	759	759	200	1640	1494	1494
500	1240	800	535	150	769	799	200	1640	1504	1534

TRANSFORMADOR PADMOUNTED TRIFASICO - MALLA												
CLASE 15/25 KV												
POTENCIA	LONGITUD CORTE	ALTURA CORTE	ANCHO CORTE	ALTURA CONCRETO	ANCHO CONCRETO			LONGITUD CONCRETO	LONGITUD TOTAL CR	ANCHO TOTAL CONCRETO		
					S/SW	SW2P	SW4P			S/SW	SW2P	SW4P
[KVA]	[mm] - [A]	[mm] - [B]	[mm] - [C]	[mm] - [D]	[mm] - [E]			[mm] - [F]	[mm] - [G]	[mm] - [H]		
30	1240	800	535	150	508	608	648	200	1640	1243	1343	1383
50	1240	800	535	150	558	608	648	200	1640	1293	1343	1383
75	1240	800	535	150	558	608	648	200	1640	1293	1343	1383
100	1240	800	535	150	558	608	648	200	1640	1293	1343	1383
125	1240	800	535	150	608	608	648	200	1640	1343	1343	1383
150	1240	800	535	150	619	689	679	200	1640	1354	1424	1414
200	1240	800	535	150	608	608	658	200	1640	1343	1343	1393
250	1240	800	535	150	649	609	719	200	1640	1384	1344	1454
300	1240	800	535	150	739	739	759	200	1640	1474	1474	1494
400	1240	800	535	150	659	739	739	200	1640	1394	1474	1474
500	1240	800	535	150	739	759	799	200	1640	1474	1494	1534

TRANSFORMAMOS EL PRESENTE,  
IMPULSAMOS EL FUTURO  
DESDE 1974

